

Obtaining a Permit

All pools constructed within the City limits require a permit prior to construction.

Separate fence permits are required for enclosure.


Property lines shall be marked to observe setbacks. Applications shall be submitted with a current plot plan, drawn to scale indicating:

- Existing structures
- Proposed pool and pool equipment with distances to lot lines
- Location of all overhead wires which cross the property
- Location and height of the fence surrounding the pool area
- Location of all gates into the pool area
- Location of all GFCI protected outlets
- Easements and building lines
- Proposed drainage if changes will be made as part of the installation.

Construction Guidelines

- Pools, pool equipment and wood decks shall not encroach into the approved side yard setback and shall be 10-feet from rear property lines and may not cross into any easements.
- Pools must be installed in the rear yard.
- Pool areas must be enclosed with a minimum 48-inch high fence. (Check with the Building Safety Department on existing fences) **Pool shall not be filled until temporary fencing is installed.**
- Gates into a pool area must open out away from the pool area and must be self-closing and self-latching with latches installed 54" above grade or 3" down from top of fence on the pool side. Double equipment gates with locks are exempt from this requirement.
- All doorways from the house to the pool area must have an alarm, separate from a home security system, that will sound when the door is opened or be self-closing and self-latching.
- All electric pool equipment must be GFCI protected and installed a minimum 6' from the pool edge with a single locking cover and grounding type receptacle. No outlets are permitted within 6 feet of the pool, and no switching or disconnecting means within 5' of the pool, but must be within sight.
- In addition to the GFCI protected outlet for the pool equipment, a GFCI protected

Example #1



- convenience outlet is required not closer than 6-feet but no more than 20-feet from the pool edge.
- Overhead power lines must be at least 10-feet horizontal from the edge of the pool or 22.5 feet in any direction of the waters edge.
- All metallic parts of the pool structure and the surrounding area, along with a perimeter bond loop shall be bonded with a #8 copper wire.
- Pool heaters shall be equipped with an accessible on/off switch, also heated pools shall be equipped with a vapor retardant cover on or at the water surface.
- Pool heaters and pumps shall be equipped with automatic timers.
- Silt control to be installed and maintained until vegetation is reestablished.
- It is not permitted to alter the flow of water to or from adjacent properties.

Pools enclosures are critical in protecting lives of children and pets. Make sure an enclosure is installed prior to filling the pool.